

FLOOR SURFACE

Wheel Material	Carpet	Linoleum	Wood	Quarry Tile	Cement	Asphalt	Terrazzo	Steel	Rough And Uneven Floors
"D" Neoprene	X	X	X	X	X	X	X	X	X
"SR" Super Roll Neoprene	X	X	X	X	X	X	X	X	X
"SE" Solid Elastomer	X	X	X		X		X	X	
"U" Polyurethane				X	X	X		X	X
"CI" Semi-Steel					X			X	
"H" Hard Rubber	X				X			X	

OPERATING CONDITIONS

Wheel Material	Temperature Range	Mobility	Durability	Floor Protection	Chemical Tolerance	Glass Or Metal Chips	Water	Steam
"D" Neoprene	-20 to +300 F	Excellent	Excellent	Excellent	Excellent	Excellent	Excellent	Excellent
"SR" Super Roll Neoprene	-20 to +300 F	Excellent	Excellent	Excellent	Excellent	Excellent	Excellent	Excellent
"SE" Solid Elastomer	-20 to +300 F	Excellent	Excellent	Excellent	Excellent	Fair	Excellent	Poor
"U" Polyurethane	-20 to +300 F	Excellent	Excellent	Very Good	Very Good	Good	Good	Poor
"CI" Semi-Steel	-20 to +300 F	Excellent	Good	Poor	Good	Good	Poor	Poor
"K" Rubber	0 to +110 F	Poor	Good	Good	Fair	Poor	Good	Good
"H" Hard Rubber	-20 to +300 F	Fair	Fair	Fair	Good	Poor	Good	Fair